NSN 5306-01-619-7785

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-619-7785

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
0.425 inches	
Fastener Length:	
0.925 inches	
Head Style:	
Double hexagon w/hole	
Head Height:	
Between 0.225 inches and 0.245 inches	
Width Between Flats:	
Between 0.347 inches and 0.361 inches	
Extended Washer Diameter:	
0.470 inches	
Extended Washer Thickness:	
Between 0.040 inches and 0.060 inches	
Hole Diameter:	
Between 0.038 inches and 0.042 inches	
Grip Diameter:	
Between 0.2481 inches and 0.2495 inches	
Single Shear Strength:	
95000 pounds per square inch	
Thread Diameter:	
0.250 inches	
Grip Length:	
0.500 inches	
Hole Quantity:	
2	
Hole Type:	
Drilled	
Thready Qty Per Inch (tpi):	
28	
Min. Tensile Strength (psi):	
160000 pounds per square inch	
Hole Configuration Style:	
Double hexagon longitudinal hole	
Material:	
Titanium alloy	
Material Specification:	
Ams 4928 assn standard single material response or ams 4	967 assn standard single material response

NSN 5306-01-619-7785

Shear Bolt - Page 2 of 2

A003b0



Surface Treatment:
Aluminum
Surface Treatment Specification:
Bms10-85, ty i, cl a mfr ref single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: