## NSN 5306-01-619-9288

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-619-9288

**Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.345 inches **Fastener Length:** 0.470 inches **Head Style:** Dished hexagon **Head Height:** Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Grip Diameter:** Between 0.1879 inches and 0.1885 inches **Shank Unthreaded Hole Diameter:** 0.070 inches all holes **Thread Diameter:** 0.190 inches **Grip Length:** 0.125 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 0.307 inches all holes **Product Name:** Bolt, hex hd, long thread, a286, 160 ksi min tensile Material: Iron alloy 660 **Material Specification:** Ams 5853 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, ty ii, cl 2 federal specification all treatment responses **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5306-01-619-9288

Shear Bolt - Page 2 of 2



|  |  |  | ure: |  |
|--|--|--|------|--|
|  |  |  |      |  |
|  |  |  |      |  |

--

Demilitarization:

No

Fiig:

A003b0