NSN 5306-01-620-2998

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-620-2998

| Thread Class |
|-----------------------------------------|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.345 inches |
| Fastener Length: |
| Between 0.518 inches and 0.548 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.110 inches and 0.125 inches |
| Width Between Flats: |
| Between 0.367 inches and 0.376 inches |
| Hole Diameter: |
| Between 0.046 inches and 0.056 inches |
| Grip Diameter: |
| Between 0.1890 inches and 0.1895 inches |
| End Application: |
| F-35 aircraft |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.178 inches and 0.198 inches |
| Hole Quantity: |
| 3 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hole Configuration Style: |
| Round |
| Material: |
| Titanium alloy uns r56400 fastener |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5306-01-620-2998

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

