NSN 5306-01-620-6591

Shear Bolt - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5306-01-620-6591
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.838 inches
Fastener Length:
3.328 inches
Head Style:
Spline extended washer
Head Height:
0.450 inches
Extended Washer Diameter:
Between 0.922 inches and 0.932 inches
Extended Washer Thickness:
Between 0.062 inches and 0.082 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
Head Minor Diameter:
Between 0.547 inches and 0.562 inches
Thread Diameter:
0.437 inches
Grip Length:
2.375 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
22640 pounds per square inch
Minimum Yield Strength:
18800 pounds per square inch
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response or ams 5663 assn standard single material response or ams 5962 assn standard single
material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:

NSN 5306-01-620-6591

Shear Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0