## NSN 5306-01-620-6591

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-620-6591

**Thread Class:** 

3a

**Thread Direction:** 

Right-hand

### Thread Length:

0.838 inches

#### Fastener Length:

3.328 inches

#### Head Style:

Spline extended washer

**Head Height:** 

0.450 inches

#### **Extended Washer Diameter:**

Between 0.922 inches and 0.932 inches

#### **Extended Washer Thickness:**

Between 0.062 inches and 0.082 inches

#### **Grip Diameter:**

Between 0.4985 inches and 0.4995 inches

#### Head Minor Diameter:

Between 0.547 inches and 0.562 inches

#### **Thread Diameter:**

0.437 inches

#### Grip Length:

2.375 inches

#### Thready Qty Per Inch (tpi):

20

#### Min. Tensile Strength (psi):

22640 pounds per square inch

#### Minimum Yield Strength:

18800 pounds per square inch

#### Material:

Nickel alloy 718

#### Material Specification:

Ams 5662 assn standard single material response or ams 5663 assn standard single material response or ams 5962 assn standard single material response

#### Surface Treatment:

Passivate

#### **Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

#### Thread Series Designator:

Unjf

#### Shelf Life:

N/a

# NSN 5306-01-620-6591

Shear Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

