NSN 5306-01-620-6592

Shear Bolt - Page 1 of 2

N/a



view Online at https://aerobasegroup.com/nsn/5506-01-620-6592
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.763 inches
Fastener Length:
4.163 inches
Head Style:
Spline extended washer
Head Height:
0.393 inches
Extended Washer Diameter:
Between 0.807 inches and 0.817 inches
Extended Washer Thickness:
Between 0.053 inches and 0.073 inches
Grip Diameter:
Between 0.4360 inches and 0.4370 inches
Head Minor Diameter:
Between 0.485 inches and 0.500 inches
Thread Diameter:
0.437 inches
Grip Length:
3.375 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
30240 pounds per square inch
Minimum Yield Strength:
24550 pounds per square inch
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response or ams 5663 assn standard single material response or ams 5962 assn standard single
material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:

NSN 5306-01-620-6592

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0