

View Online at <https://aerobasegroup.com/nsn/5306-01-620-7449>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.469 inches

**Fastener Length:**

Between 4.329 inches and 4.359 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.156 inches and 0.171 inches

**Width Between Flats:**

Between 0.492 inches and 0.502 inches

**Grip Diameter:**

Between 0.3110 inches and 0.3120 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches and 0.086 inches all holes

**Thread Diameter:**

0.3125 inches

**Grip Length:**

Between 3.865 inches and 3.885 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

95000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.171 inches and 0.191 inches all holes

**Product Name:**

Bolt, hex head

**Material:**

Steel comp 4140 or steel comp 4340 or steel comp e4340 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification 1st material response or ams6415 assn standard 2nd material response or mil-s-5000 military specification 3rd material response or mil-s-6049 military specification 4th material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.