

View Online at <https://aerobasegroup.com/nsn/5306-01-621-5517>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.560 inches

**Fastener Length:**

Between 1.67 inches and 1.70 inches

**Head Style:**

Double hexagon extended washer

**Head Height:**

Between 0.388 inches and 0.398 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Extended Washer Diameter:**

Between 0.639 inches and 0.649 inches

**Extended Washer Thickness:**

Between 0.081 inches and 0.101 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**End Application:**

A10

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 1.115 inches and 1.135 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Surface Finish:**

32.0 microinches threads

**Product Name:**

Bolt, tension, 12 point external wrenching, 220ksi min-482 deg. C

**Material:**

Nickel alloy 718

**Material Specification:**

Vms 110 mfr ref single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Nas672 national std/spec single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0