## NSN 5306-01-621-8869

Shear Bolt - Page 1 of 2



**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** 0.993 inches **Fastener Length:** 6.618 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.701 inches and 0.721 inches Width Between Flats: Between 0.808 inches and 0.817 inches **Extended Washer Diameter:** Between 1.220 inches and 1.230 inches **Extended Washer Thickness:** Between 0.168 inches and 0.188 inches Hole Diameter: Between 0.050 inches and 0.060 inches **Grip Diameter:** Between 0.748 inches and 0.749 inches **End Application:** B-1 **Thread Diameter:** 0.750 inches Grip Length: Between 5.615 inches and 5.635 inches Hole Type: Drilled Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 180000 pounds per square inch **Product Name:** Bolt twelve point Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate **Thread Series Designator:** 

Unjf



## NSN 5306-01-621-8869

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

