## NSN 5306-01-621-9973

Shear Bolt - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5306-01-621-9973  |
|--|
| Thread Class:  |
| Y3a  |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.454 inches   |
| Fastener Length:   |
| 1.204 inches   |
| Head Style:  |
| Dished hexagon   |
| Head Height:   |
| 0.188 inches   |
| Width Between Flats:   |
| Between 0.554 inches and 0.564 inches  |
| Hole Diameter:   |
| Between 0.070 inches and 0.080 inches  |
| Grip Diameter:   |
| Between 0.3740 inches and 0.3745 inches  |
| End Application:   |
| C-5 reliability enhancement re-engining program  |
| Thread Diameter:   |
| 0.3750 inches  |
| Grip Length:   |
| 0.750 inches   |
| Thready Qty Per Inch (tpi):  |
| E24  |
| Surface Finish:  |
| 32.0 microinches bearing surface of head   |
| Product Name:  |
| Bolt, tension, hex head, close tolerance, a286 cres, short thread, reduced major thread dia, 160 ksi ftu                         |
| Material:  |
| Stainless steel  |
| Material Specification:  |
| Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single |
| material response or ams5853 assn standard single material response  |
| Surface Treatment:   |
| Passivate  |
| Surface Treatment Specification:   |
| Ams 2700, method 1, type 2 or type 8, class 1 assn standard single treatment response  |
| Thread Series Designator:  |
| Unjf   |
| Shelf Life:  |

N/a

## NSN 5306-01-621-9973

Shear Bolt - Page 2 of 2



|    | • • |             |    |     |      |
|----|-----|-------------|----|-----|------|
| In | 18  | <i>(</i> )+ | МА | 261 | ıre: |
|    |     |             |    |     |      |

--

Demilitarization:

No

Fiig:

A003b0