NSN 5306-01-621-9973

Shear Bolt - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5306-01-621-9973 |
|--|
| Thread Class: |
| Y3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.454 inches |
| Fastener Length: |
| 1.204 inches |
| Head Style: |
| Dished hexagon |
| Head Height: |
| 0.188 inches |
| Width Between Flats: |
| Between 0.554 inches and 0.564 inches |
| Hole Diameter: |
| Between 0.070 inches and 0.080 inches |
| Grip Diameter: |
| Between 0.3740 inches and 0.3745 inches |
| End Application: |
| C-5 reliability enhancement re-engining program |
| Thread Diameter: |
| 0.3750 inches |
| Grip Length: |
| 0.750 inches |
| Thready Qty Per Inch (tpi): |
| E24 |
| Surface Finish: |
| 32.0 microinches bearing surface of head |
| Product Name: |
| Bolt, tension, hex head, close tolerance, a286 cres, short thread, reduced major thread dia, 160 ksi ftu |
| Material: |
| Stainless steel |
| Material Specification: |
| Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single |
| material response or ams5853 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Ams 2700, method 1, type 2 or type 8, class 1 assn standard single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |

N/a

NSN 5306-01-621-9973

Shear Bolt - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A003b0