

View Online at <https://aerobasegroup.com/nsn/5306-01-622-5590>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.578 inches

Fastener Length:

Between 1.625 inches and 1.655 inches

Head Style:

Hexagon

Head Height:

Between 0.188 inches and 0.203 inches

Width Between Flats:

Between 0.554 inches and 0.564 inches

Locking Feature:

Patch locking feature

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Thread Diameter:

0.3750 inches

Grip Length:

Between 1.0525 inches and 1.0725 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Surface Finish:

32.0 microinches threads

Product Name:

Bolt, tension, hex head, close tolerance, alloy steel, long thread, reduced major dia., self-locking and nonlocking, 160 ksi ftu

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740 fastener

Material Specification:

Ams6349 or 6382 national std/spec 1st material response or ams6415 or 6484 national std/spec 2nd material response or ams6322 national std/spec 3rd material response fastener

Surface Treatment:

Cadmium fastener

Surface Treatment Specification:

Qq-p-416, type ii, class 2; embrittlement requirement per nas4002 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Specification Data:

80205-nas6603 through 6620 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-dtl-18240 spec.