

View Online at <https://aerobasegroup.com/nsn/5306-01-622-9217>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.528 inches

Fastener Length:

Between 1.201 inches and 1.231 inches

Head Style:

Hexagon

Head Height:

Between 0.250 inches and 0.265 inches

Width Between Flats:

Between 0.741 inches and 0.752 inches

Grip Diameter:

Between 0.4990 inches and 0.4995 inches

Shank Unthreaded Hole Diameter:

0.106 inches and 0.116 inches all holes

Thread Diameter:

0.500 inches

Grip Length:

Between 0.678 inches and 0.698 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.018 inches all holes

Surface Finish:

32.0 microinches threads

Product Name:

Bolt, tension, hex head, close tolerance, a286 cres, short thread, reduced major thread dia., self-locking and nonlocking, 160ksi ftu

Material:

Iron alloy 660

Material Specification:

Ams5731 national std/spec single material response or ams5732 national std/spec single material response or ams5737 national std/spec single material response or ams5853 national std/spec single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Ams2700, method i, type 2 or 8, class 1 national std/spec single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6303 through 6320 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0