## NSN 5306-01-623-2129

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-623-2129

Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

0.659 inches

### Fastener Length:

2.559 inches

#### Head Style:

Spline extended washer

**Head Height:** 

0.070 inches

## **Extended Washer Diameter:**

Between 0.691 inches and 0.701 inches

## **Extended Washer Thickness:**

Between 0.044 inches and 0.064 inches

#### **Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

## Single Shear Strength:

13825 pounds per square inch

## Head Minor Diameter:

Between 0.423 inches and 0.438 inches

## Thread Diameter:

0.375 inches

## Grip Length:

1.875 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

## Material:

Nickel alloy 718

## Material Specification:

Ams 5662 assn standard single material response or ams 5663 assn standard single material response

## Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5306-01-623-2129

Shear Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

