## NSN 5306-01-625-0836

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-625-0836

Thread Class:
Q3a
Thread Direction:
Right-hand
Thread Length:
0.551 inches
Fastener Length:
1.489 inches
Head Style:
Double hexagon w/hole
Head Height:
0.348 inches
Width Between Flats:
0.376 inches
Extended Washer Diameter:
0.526 inches
Extended Washer Thickness:
0.082 inches
Hole Diameter:
0.215 inches
Grip Diameter:
Between 0.3115 inches and 0.3120 inches
End Application:
F-15sa
Thread Diameter:
0.3125 inches
Grip Length:
0.938 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
M24
Min. Tensile Strength (psi):
220 pounds per square inch
Hole Configuration Style:
Double hexagon longitudinal hole
Product Name:
Bolt-close tolerance, 12 pt, flange head, 220 ksi ftu cres
Material:
Steel comp xm-13

## NSN 5306-01-625-0836

Shear Bolt - Page 2 of 2

Fiig: A003b0



Material Specification:
Ams5629 federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Ams2700 method 1 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No