## NSN 5306-01-625-5590

Shear Bolt - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5306-01-625-5590

**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

0.763 inches

#### **Fastener Length:**

4.163 inches

#### **Head Style:**

Spline extended washer

**Head Height:** 

0.393 inches

#### **Extended Washer Diameter:**

Between 0.807 inches and 0.817 inches

#### **Extended Washer Thickness:**

Between 0.053 inches and 0.073 inches

#### **Grip Diameter:**

Between 0.4360 inches and 0.4370 inches

#### Head Minor Diameter:

Between 0.485 inches and 0.500 inches

#### **Thread Diameter:**

0.437 inches

## Grip Length:

3.375 inches

## Thready Qty Per Inch (tpi):

20

## Min. Tensile Strength (psi):

30240 pounds per square inch

## Minimum Yield Strength:

245550 pounds per square inch

#### Material:

Nickel alloy 718

## Material Specification:

Ams5662 assn standard single material response or ams5663 assn standard single material response or ams5962 assn standard single material response

#### **Surface Treatment:**

Passivate

## **Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

## Thread Series Designator:

Unjf

#### Shelf Life:

N/a

# NSN 5306-01-625-5590

Shear Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

