

View Online at <https://aerobasegroup.com/nsn/5306-01-625-5591>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.838 inches

Fastener Length:

Between 1.723 inches and 1.753 inches

Head Style:

Spline extended washer

Head Height:

Between 0.440 inches and 0.460 inches

Extended Washer Diameter:

Between 0.922 inches and 0.932 inches

Extended Washer Thickness:

Between 0.062 inches and 0.082 inches

Hole Diameter:

Between 0.060 inches and 0.070 inches

Grip Diameter:

Between 0.4985 inches and 0.4995 inches

Head Minor Diameter:

Between 0.547 inches and 0.562 inches

Thread Diameter:

0.7500 inches

Grip Length:

Between 0.865 inches and 0.885 inches

Hole Quantity:

4

Hole Type:

Drilled

Features Provided:

Dry film lubricant

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

220000 pounds per square inch

Hole Configuration Style:

Spline

Product Name:

Bolt, tension

Material:

Nickel alloy 718

Material Specification:

Ams5662 assn standard single material response or ams5663 assn standard single material response or ams5962 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Ams2700, method 1, type 2 or type 8, class 4 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0