

View Online at <https://aerobasegroup.com/nsn/5306-01-625-5595>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.005 inches

**Fastener Length:**

Between 2.390 inches and 2.420 inches

**Head Style:**

Spline extended washer

**Head Height:**

Between 0.552 inches and 0.572 inches

**Extended Washer Diameter:**

Between 1.153 inches and 1.163 inches

**Extended Washer Thickness:**

Between 0.080 inches and 0.108 inches

**Hole Diameter:**

Between 0.060 inches and 0.070 inches

**Grip Diameter:**

Between 0.6230 inches and 0.6240 inches

**Head Minor Diameter:**

Between 0.673 inches and 0.688 inches

**Thread Diameter:**

0.6250 inches

**Grip Length:**

Between 1.365 inches and 1.385 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Features Provided:**

Dry film lubricant

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hole Configuration Style:**

Spline

**Product Name:**

Bolt, tension

**Material:**

Nickel alloy 718

**Material Specification:**

Ams5662 assn standard single material response or ams5663 assn standard single material response or ams5962 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Ams2700, method 1, type 2 or type 8, class 4 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0