NSN 5306-01-625-5595

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-625-5595 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.005 inches **Fastener Length:** Between 2.390 inches and 2.420 inches **Head Style:** Spline extended washer **Head Height:** Between 0.552 inches and 0.572 inches **Extended Washer Diameter:** Between 1.153 inches and 1.163 inches **Extended Washer Thickness:** Between 0.080 inches and 0.108 inches **Hole Diameter:** Between 0.060 inches and 0.070 inches **Grip Diameter:** Between 0.6230 inches and 0.6240 inches **Head Minor Diameter:** Between 0.673 inches and 0.688 inches **Thread Diameter:** 0.6250 inches **Grip Length:** Between 1.365 inches and 1.385 inches **Hole Quantity:** Hole Type: Drilled **Features Provided:** Dry film lubricant Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 220000 pounds per square inch **Hole Configuration Style:** Spline **Product Name:** Bolt, tension

Material: Nickel alloy 718

NSN 5306-01-625-5595

Shear Bolt - Page 2 of 2



Ams5662 assn standard single material response or ams5663 assn standard single material response or ams5962 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Ams2700, method 1, type 2 or type 8, class 4 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0