## NSN 5306-01-625-8012



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-625-8012 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.501 inches **Fastener Length:** Between 1.111 inches and 1.141 inches **Head Style:** Flat countersunk **Head Diameter:** 0.4787 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Thread Diameter:** 0.3125 inches **Grip Length:** 0.625 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Bolt, shear Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 **Material Specification:** Ams6382 assn standard 1st material response or ams6415 assn standard 2nd material response or ams6484 assn standard 2nd material response or ams6322 assn standard 3rd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams-qq-p-416, type 2, class 2 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life:

**Demilitarization:** No

**Unit Of Measure:** 

N/a

## NSN 5306-01-625-8012

Shear Bolt - Page 2 of 2



Fiig:

A003b0