

View Online at <https://aerobasegroup.com/nsn/5306-01-625-8544>

**Thread Class:**

R3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.331 inches

**Fastener Length:**

Between 1.940 inches and 1.987 inches

**Head Style:**

Double hexagon

**Head Height:**

0.140 inches

**Width Between Flats:**

0.376 inches

**Grip Diameter:**

Between 0.1890 inches and 0.1895 inches

**Point Diameter:**

0.1900 inches

**Shank Unthreaded Hole Diameter:**

0.070 inches and 0.075 inches ring

**Point Style:**

Flat

**End Application:**

F-15sa

**Thread Diameter:**

0.1900 inches

**Grip Length:**

1.625 inches

**Thready Qty Per Inch (tpi):**

N32

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.111 inches and 0.121 inches point

**Product Name:**

Bolt, close tolerance, double hex head

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 federal specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0