

View Online at <https://aerobasegroup.com/nsn/5306-01-628-5844>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.468 inches

Fastener Length:

Between 1.360 inches and 1.390 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.485 inches and 0.500 inches

Width Between Flats:

0.562 inches

Extended Washer Diameter:

Between 0.428 inches and 0.438 inches

Extended Washer Thickness:

Between 0.182 inches and 0.192 inches

Shoulder Diameter:

0.427 inches and 0.438 inches first shoulder

Shoulder Length:

0.182 inches and 0.192 inches first shoulder

Hole Diameter:

0.055 inches

Thread Diameter:

0.250 inches

Hole Quantity:

4

Hole Type:

Drilled

Nonstandard Thread Pitch Diameter:

+0.2243 to 0.2268 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

200000 pounds per square inch

Hole Configuration Style:

Double hexagon flats

Shoulder Shape:

Round first shoulder

Product Name:

Bolt, 12 point flange head, 0.0312 oversize, 200 ksi ftu, cres

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0