NSN 5306-01-628-6534

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-628-6534 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.454 inches **Fastener Length:** Between 2.086 inches and 2.106 inches **Head Style:** Hexagon **Head Height:** Between 0.188 inches and 0.203 inches Width Between Flats: Between 0.554 inches and 0.564 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **End Application:** Air-atr-72-600; stabilizer **Thread Diameter:** 0.375 inches **Grip Length:** Between 1.632 inches and 1.652 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Product Name:** Bolt, tension, hex head, close tolerance, 6al-4v titanium alloy, short thread, reduced major thread diameter, nonlocking, 160 ksi ftu Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 or ams4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Nas4006 assn standard single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

Unit Of Measure:

NSN 5306-01-628-6534

Shear Bolt - Page 2 of 2



| _ | | | | | | |
|----|-----|---------|-----|-----|----|--|
| 11 | em) | tor | 172 | + 1 | nn | |
| | | | | | | |

No

Fiig:

A003b0