## NSN 5306-01-628-6534

Shear Bolt - Page 1 of 2

---



View Online at https://aerobasegroup.com/nsn/5306-01-628-6534

	://aerobasegroup.com/nsn/5306-01-628-6534
Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
0.454 inches	
Fastener Length:	
Between 2.086 inche	es and 2.106 inches
Head Style:	
Hexagon	
Head Height:	
Between 0.188 inche	es and 0.203 inches
Width Between Fla	ts:
Between 0.554 inche	es and 0.564 inches
Grip Diameter:	
Between 0.3735 incl	nes and 0.3745 inches
End Application:	
Air-atr-72-600; stab	ilizer
Thread Diameter:	
0.375 inches	
Grip Length:	
Between 1.632 inche	es and 1.652 inches
Thready Qty Per In	ch (tpi):
24	
Min. Tensile Streng	ıth (psi):
160000 pounds per	square inch
Product Name:	
Bolt, tension, hex h	ead, close tolerance, 6al-4v titanium alloy, short thread, reduced major thread diameter, nonlocking, 160 ksi ftu
Material:	
Titanium alloy uns r	56400
Material Specificati	on:
Ams4928 or ams496	67 assn standard single material response
Surface Treatment:	
Aluminum	
Surface Treatment	Specification:
Nas4006 assn stanc	lard single treatment response
Thread Series Desi	gnator:
Unjf	
Shelf Life:	
N/a	
Unit Of Measure:	

## NSN 5306-01-628-6534

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

