NSN 5306-01-628-6585



Close Tolerance Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-628-6585 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.767 inches **Fastener Length:** Between 2.502 inches and 2.532 inches **Head Style:** Double hexagon extended washer **Head Height:** 0.504 inches Width Between Flats: 0.632 inches **Extended Washer Diameter:** Between 0.827 inches and 0.837 inches **Extended Washer Thickness:** 0.123 inches **Grip Diameter:** Between 0.4990 inches and 0.4995 inches Point Length: 0.060 inches **Point Style:** Flat **End Application:** F-15sa **Thread Diameter:** 0.500 inches **Grip Length:** 1.750 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 19640 pounds per square inch **Point Chamfer Angle:** 45.0 degrees **Product Name:** Bolt, close tolerance, 12 point, flange head, 220 ksi ftu, cres Material:

Steel comp xm-13

Material Specification:

Ams 5629 federal standard single material response

NSN 5306-01-628-6585

Close Tolerance Bolt - Page 2 of 2

Fiig: A003b0



Surface Treatment:
Passivate
Surface Treatment Specification:
Ams 2700 method 1 federal standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No