NSN 5306-01-629-8491

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-629-8491

| view Offilite at https://aerobasegroup.com/hsr//3000-01-023-0431 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.500 inches |
| Fastener Length: |
| Between 1.5475 inches and 1.5775 inches |
| Head Style: |
| Double hexagon w/hole |
| Head Height: |
| Between 0.225 inches and 0.245 inches |
| Width Between Flats: |
| Between 0.305 inches and 0.313 inches |
| Extended Washer Diameter: |
| Between 0.465 inches and 0.475 inches |
| Extended Washer Thickness: |
| Between 0.032 inches and 0.052 inches |
| Grip Diameter: |
| Between 0.2481 inches and 0.2495 inches |
| End Application: |
| 1520-01-457-5179 |
| Thread Diameter: |
| 0.2500 inches |
| Grip Length: |
| Between 1.0525 inches and 1.0725 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 200000 pounds per square inch |
| Product Name: |
| Bolt, 12 point head |
| Material: |
| Stainless steel |
| Material Specification: |
| Ams 5737 assn standard single material response |
| Surface Treatment: |
| Aluminum |
| Surface Treatment Specification: |
| Bms10-85, type 1, class a or class b mfr ref single treatment response |
| Thread Series Designator: |
| 119 |

Unjf

NSN 5306-01-629-8491

Shear Bolt - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0