
NSN 5306-01-629-8491

Shear Bolt - Page 1 of 2

3a





Thread Class: Thread Direction: Right-hand Thread Length: 0.500 inches Fastener Length: Between 1.5475 inches and 1.5775 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.225 inches and 0.245 inches Width Between Flats: Between 0.305 inches and 0.313 inches **Extended Washer Diameter:** Between 0.465 inches and 0.475 inches **Extended Washer Thickness:** Between 0.032 inches and 0.052 inches Grip Diameter: Between 0.2481 inches and 0.2495 inches **End Application:** 1520-01-457-5179 **Thread Diameter:** 0.2500 inches Grip Length: Between 1.0525 inches and 1.0725 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 200000 pounds per square inch **Product Name:** Bolt, 12 point head Material: Stainless steel **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Bms10-85, type 1, class a or class b mfr ref single treatment response **Thread Series Designator:**

Unjf

28

NSN 5306-01-629-8491

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

