## NSN 5306-01-631-3893



Shear Bolt - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5306-01-631-3893 **Thread Direction:** Right-hand Thread Length: Between 0.68 inches and 0.88 inches **Fastener Length:** Between 1.9925 inches and 2.1925 inches **Head Style:** Countersunk cylindrical convex **Locking Feature:** Slotted locking feature **Grip Diameter:** Between 0.1625 inches and 0.1635 inches **Head Major Diameter:** Between 0.2532 inches and 0.2605 inches **End Application:** 1520-01-457-5179 **Thread Diameter:** 0.1640 inches **Grip Length:** Between 1.3075 inches and 1.3175 inches **Countersink Angle:** 100.0 degrees **Product Name:** Bolt, lock, 100 degrees head **Special Features:** Bolt has a shear strength of 95000psi. Finish is designated by yellow dye or paint on a portion of the pintail. Threaded portion breaks off after bolt is inserted. Bolt is kept in place by grooves. Maximum service temp is 250 degrees f. Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Bms10-85, type 1, class a mfr ref single treatment response Shelf Life: N/a **Unit Of Measure:** 

Fiig: A003b0

No

**Demilitarization:**