NSN 5306-01-633-1162

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-633-1162

| Thread Class. |
|--|
| Thread Class: |
| 3a Through Directions |
| Thread Direction: |
| Right-hand Thread Longton |
| Thread Length: |
| 0.528 inches |
| Fastener Length: |
| Between 2.013 inches and 2.043 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.250 inches and 0.265 inches |
| Width Between Flats: |
| Between 0.741 inches and 0.752 inches |
| Grip Diameter: |
| Between 0.5141 inches and 0.5151 inches |
| End Application: |
| Kc-135 acft |
| Thread Diameter: |
| 0.5000 inches |
| Grip Length: |
| Between 1.490 inches and 1.510 inches |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Product Name: |
| Bolt, tension, hex head |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams4928 assn standard single material response or ams4967 assn standard single material response |
| Surface Treatment: |
| Aluminum |
| Surface Treatment Specification: |
| Nas4006 assn standard single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5306-01-633-1162

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0