NSN 5306-01-641-8227

Assembled Sleeve Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-641-8227

view Offilite at https://aerobasegroup.com/hist//5500-01-041-022/
Thread Class:
3b
Thread Direction:
Right-hand
Head Style:
Flat
Head Diameter:
0.399 inches
Head Height:
0.045 inches
Lubrication:
Dry film lubricant
Nut Style:
Blind rivet w/hex shank
Nut Length:
0.611 inches
Unable To Decode:
+0.245 to 0.255 inches
Shank End Type:
Closed
Width Across Flats:
0.1875 inches
Thread Series:
Unjf
Thready Qty Per Inch (tpi):
32
Thread Size:
0.1900 inches
Product Name:
Stud nut a286 cres steel, hex recess
Special Features:
Dry film lubricant iaw as5272, type i; anti-seize compound per mil-a-907 applied to internal threads; designed for use with a ca167 ()
retaining ring; dimensions apply before dry film lubricant; thread length is 0.400 inches
Material:
Iron alloy 660
Material Specification:
Cres a286 iaw ams5731 national std/spec single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Ams-qq-p-35 national specification single treatment response
Shelf Life:

N/a

NSN 5306-01-641-8227

Assembled Sleeve Bolt - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A003b0