NSN 5306-01-641-8227

Assembled Sleeve Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-641-8227

| Assembled Sleeve Bolt |
|---------------------------------|
| View Online at https://aerobase |
| Thread Class: |
| 3b |
| Thread Direction: |
| Right-hand |
| Head Style: |
| Flat |
| Head Diameter: |
| 0.399 inches |
| Head Height: |
| 0.045 inches |
| Lubrication: |
| Dry film lubricant |
| Nut Style: |
| Blind rivet w/hex shank |
| Nut Length: |
| 0.611 inches |
| Unable To Decode: |
| +0.245 to 0.255 inches |
| Shank End Type: |
| Closed |
| Width Across Flats: |
| 0.1875 inches |
| Thread Series: |
| Unjf |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.1900 inches |
| Due due (New et |

Product Name:

Stud nut a286 cres steel, hex recess

Special Features:

Dry film lubricant iaw as5272, type i; anti-seize compound per mil-a-907 applied to internal threads; designed for use with a ca167 ()

retaining ring; dimensions apply before dry film lubricant; thread length is 0.400 inches

Material:

Iron alloy 660

Material Specification:

Cres a286 iaw ams5731 national std/spec single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Ams-qq-p-35 national specification single treatment response

Shelf Life:

N/a

NSN 5306-01-641-8227

Assembled Sleeve Bolt - Page 2 of 2

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

