

View Online at <https://aerobasegroup.com/nsn/5306-01-642-4288>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.578 inches

Fastener Length:

Between 1.188 inches and 1.218 inches

Head Style:

Hexagon

Head Height:

Between 0.188 inches and 0.203 inches

Width Between Flats:

Between 0.554 inches and 0.564 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Thread Diameter:

0.3750 inches

Grip Length:

Between 0.615 inches and 0.635 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Surface Finish:

32.0 microinches threads

Product Name:

Bolt, hex head, close tolerance, a286 cres, long threads, self-locking and nonlocking

Special Features:

Bolt has 95 ksi ultimate shear strength; 160-190 ksi ftu tensile strength; precipitation hardened per ams5853

Material:

Iron alloy 660

Material Specification:

Cres a28 (uns s66286) iaw ams5731, 5732, 5737 or 5853 national standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Nas4006 national std/spec single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6703 through 6720 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0