

View Online at <https://aerobasegroup.com/nsn/5306-01-642-4288>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.578 inches

**Fastener Length:**

Between 1.188 inches and 1.218 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.188 inches and 0.203 inches

**Width Between Flats:**

Between 0.554 inches and 0.564 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Thread Diameter:**

0.3750 inches

**Grip Length:**

Between 0.615 inches and 0.635 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Surface Finish:**

32.0 microinches threads

**Product Name:**

Bolt, hex head, close tolerance, a286 cres, long threads, self-locking and nonlocking

**Special Features:**

Bolt has 95 ksi ultimate shear strength; 160-190 ksi ftu tensile strength; precipitation hardened per ams5853

**Material:**

Iron alloy 660

**Material Specification:**

Cres a28 (uns s66286) iaw ams5731, 5732, 5737 or 5853 national standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Nas4006 national std/spec single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6703 through 6720 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0