## NSN 5306-01-645-6847

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-645-6847

Class:

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

0.408 inches

#### Fastener Length:

1.091 inches

#### Head Style:

Spline extended washer

#### Head Height:

Between 0.195 inches and 0.215 inches

#### **Extended Washer Diameter:**

Between 0.349 inches and 0.359 inches

#### **Extended Washer Thickness:**

Between 0.017 inches and 0.037 inches

#### Hole Diameter:

Between 0.032 inches and 0.042 inches

#### Grip Diameter:

Between 0.1885 inches and 0.1895 inches

## Head Minor Diameter:

Between 0.173 inches and 0.188 inches

#### **Thread Diameter:**

0.1900 inches

#### Grip Length:

Between 0.668 inches and 0.698 inches

#### Hole Quantity:

4

#### Hole Type:

Drilled

#### Thready Qty Per Inch (tpi):

32

## Min. Tensile Strength (psi):

220000 pounds per square inch

## Hole Configuration Style:

Spline

## Product Name:

Bolt, tension

Material:

Nickel alloy 718

## Material Specification:

Ams 5662 assn standard single material response or ams 5663 assn standard single material response

# NSN 5306-01-645-6847

Shear Bolt - Page 2 of 2



Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0