
## NSN 5306-01-645-7134

Shear Bolt - Page 1 of 2

**Thread Class:** 





3a **Thread Direction: Right-hand Thread Length:** Between 0.375 inches and 0.405 inches Fastener Length: 0.952 inches **Head Style:** Double hexagon extended washer **Head Height:** 0.196 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** Between 0.340 inches and 0.350 inches **Extended Washer Thickness:** 0.064 inches Hole Diameter: Between 0.034 inches and 0.042 inches **Grip Diameter:** 0.188 inches **Thread Diameter:** 0.190 inches Grip Length: 0.438 inches **Hole Quantity:** 4 Hole Type: Drilled Nonstandard Thread Pitch Diameter: +0.1674 to 0.1697 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 220000 pounds per square inch Hole Configuration Style: Double hexagon longitudinal hole **Product Name:** B1-b aircraft Material: Steel comp xm-13

## NSN 5306-01-645-7134

Shear Bolt - Page 2 of 2



Material Specification: Ams5629 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A003b0