NSN 5306-01-649-3034



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-649-3034 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.454 inches **Fastener Length:** Between 1.501 inches and 1.531 inches **Head Style:** Dished hexagon **Head Height:** Between 0.188 inches and 0.203 inches Width Between Flats: Between 0.554 inches and 0.564 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches threads **Product Name:** Bolt, tension, hex head Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 **Material Specification:** Ams6349 assn standard 1st material response or ams6415 assn standard 2nd material response or ams6322 assn standard 3rd material response **Surface Treatment:** Chromium grip **Surface Treatment Specification:** Ams-qq-p-146, type ii, class 2 assn standard single treatment response threads **Thread Series Designator:** Unjf

N/a

Shelf Life:

Unit Of Measure:

NSN 5306-01-649-3034

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0