NSN 5306-01-649-8022

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-649-8022 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.249 inches and 0.269 inches **Fastener Length:** 0.438 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.330 inches Width Between Flats: Between 0.305 inches and 0.313 inches **Extended Washer Diameter:** 0.438 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches **Grip Diameter:** Between 0.222 inches and 0.232 inches **End Application:** Kc-46a tanker **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.079 inches and 0.099 inches Thready Qty Per Inch (tpi): 28 **Hardness Rating:**

42.0 rockwell c and 46.0 rockwell c bearing surface of head

Surface Finish:

32.0 microinches grip

Product Name:

Bolt, machine-steel ams6304, diffused nickel-cadmium plated, double hexagon extended washer head

Special Features:

O'level ata-75

Material:

Steel comp 601

Material Specification:

Ams6304 assn standard single material response

Surface Treatment:

Cadmium and nickel

NSN 5306-01-649-8022

Machine Bolt - Page 2 of 2



Surface Treatment Speci

Ams2416 assn standard single treatment response

Thread Series Designator:

Unjf

Reference Number Differentiating Characteristics:

Item is faa certified

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0