

View Online at <https://aerobasegroup.com/nsn/5306-01-651-5394>

Thread Class:

4h6h

Thread Direction:

Right-hand

Thread Length:

14.50 millimeters

Fastener Length:

Between 52.2 millimeters and 52.8 millimeters

Head Style:

Hexagon

Head Height:

Between 4.7 millimeters and 5.0 millimeters

Width Between Flats:

Between 16.73 millimeters and 17.00 millimeters

Grip Diameter:

Between 9.962 millimeters and 9.987 millimeters

Point Diameter:

Between 7.9 millimeters and 8.4 millimeters

Point Style:

Flat

End Application:

1055-01-536-7106

Thread Diameter:

10.0 millimeters

Grip Length:

Between 37.7 millimeters and 38.3 millimeters

Min. Tensile Strength (psi):

1100 megapascals

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Thread Pitch In Millimeters:

1.25

Surface Finish:

0.8 micrometers fastener

Product Name:

Bolt, close tolerance, hexagon head, alloy steel, 1100mpa, metric

Special Features:

Alloy of steel to be specified at time of procurement

Material:

Steel

Surface Treatment:

Cadmium

Surface Treatment Specification:

Sae-ams-qq-p-416, type ii, class 2 national std/spec single treatment response

Thread Series Designator:

Mj

Specification Data:

80205-na0036 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A003b0