## NSN 5306-01-651-9784

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-651-9784 **Thread Direction:** Right-hand Thread Length: 11.5 millimeters Fastener Length: Between 39.2 millimeters and 39.8 millimeters **Head Style:** Hexagon **Head Height:** Between 4.2 millimeters and 4.5 millimeters Width Between Flats: Between 12.73 millimeters and 13.00 millimeters **Grip Diameter:** Between 7.962 millimeters and 7.987 millimeters **Point Diameter:** Between 6.2 millimeters and 6.7 millimeters Point Style: Flat **End Application:** 1055-01-536-7106 **Thread Diameter:** 8.0 millimeters **Grip Length:** Between 27.8 millimeters and 28.2 millimeters Min. Tensile Strength (psi): 1100 megapascals Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Thread Pitch In Millimeters:** 1.0 **External Thread Tolerance Class:** 4h6h **Surface Finish:** 0.8 micrometers fastener **Product Name:** Bolt, close tolerance, hexagon head, alloy steel, 1100 mpa, metric **Special Features:** Alloy steel per procurement specification Material: Steel

**Surface Treatment:** 

Cadmium

## NSN 5306-01-651-9784

Close Tolerance Bolt - Page 2 of 2



Ams-qq-p-416, type ii, class 2 national standard single treatment response

**Thread Series Designator:** 

Mj

**Specification Data:** 

80205-na0036 national std/spec

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A003b0