

View Online at <https://aerobasegroup.com/nsn/5306-01-653-7344>

**Thread Class:**

4h6h

**Thread Direction:**

Right-hand

**Thread Length:**

10.0 millimeters

**Fastener Length:**

Between 27.7 millimeters and 28.3 millimeters

**Head Style:**

Hexagon

**Head Height:**

Between 3.2 millimeters and 3.5 millimeters

**Width Between Flats:**

Between 9.78 millimeters and 10.00 millimeters

**Grip Diameter:**

Between 5.965 millimeters and 5.990 millimeters

**Point Diameter:**

Between 4.2 millimeters and 4.7 millimeters

**Point Style:**

Flat

**Internal Drive Style:**

W/o internal drive

**End Application:**

1055-01-536-7106

**Thread Diameter:**

6.0 millimeters

**Grip Length:**

Between 17.8 millimeters and 18.2 millimeters

**Min. Tensile Strength (psi):**

1100 megapascals

**Thread Pitch In Millimeters:**

1.0

**Surface Finish:**

0.8 micrometers

**Product Name:**

Bolt, close tolerance, hexagon head, a286 cres, 1100 mpa, metric

**Material:**

Stainless steel

**Material Specification:**

Na0026 national standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Ams2700, method 1, class 4 national standard single treatment response

**Thread Series Designator:**

Mj

**Specification Data:**

80205-na0045 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0