## NSN 5306-01-654-3461

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-654-3461

| Thread Class:                         |
|---------------------------------------|
| 3a                                    |
| Thread Direction:                     |
| Right-hand                            |
| Thread Length:                        |
| 0.500 inches                          |
| Fastener Length:                      |
| Between 0.923 inches and 0.953 inches |
| Head Style:                           |
| Double hexagon w/hole                 |
| Head Height:                          |
| Between 0.224 inches and 0.244 inches |
| Width Between Flats:                  |
| 0.312 inches                          |
| Extended Washer Diameter:             |
| Between 0.428 inches and 0.438 inches |
| Extended Washer Thickness:            |
| Between 0.059 inches and 0.079 inches |
| Grip Diameter:                        |
| Between 0.249 inches and 0.250 inches |
| End Application:                      |
| B1-bacft                              |
| Thread Diameter:                      |
| 0.250 inches                          |
| Grip Length:                          |
| Between 0.428 inches and 0.448 inches |
| Thready Qty Per Inch (tpi):           |
| 28                                    |
| Min. Tensile Strength (psi):          |
| 180000 pounds per square inch         |
| Product Name:                         |
| Bolt-tension, external wrenching      |
| Material:                             |
| Nickel alloy 718                      |
| Surface Treatment:                    |
| Passivate                             |
| Thread Series Designator:             |
| -                                     |
| Unjf<br>Shelf Life:                   |
| Sheli Lire:<br>N/a                    |
| Unit Of Measure:                      |
| Unit Ul Medsule.                      |
|                                       |

## NSN 5306-01-654-3461

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

