

View Online at <https://aerobasegroup.com/nsn/5306-01-654-6192>

Thread Class:

4h6h

Thread Direction:

Right-hand

Thread Length:

16.0 inches

Fastener Length:

Between 115.7 millimeters and 116.3 millimeters

Head Style:

Hexagon

Head Height:

Between 5.7 millimeters and 6.0 millimeters

Width Between Flats:

Between 18.67 millimeters and 19.00 millimeters

Grip Diameter:

Between 11.959 millimeters and 11.984 millimeters

Point Diameter:

Between 9.9 millimeters and 10.4 millimeters

Point Style:

Flat

Internal Drive Style:

W/o internal drive

End Application:

1055-01-536-7106

Thread Diameter:

12.0 millimeters

Grip Length:

Between 99.8 millimeters and 100.2 millimeters

Min. Tensile Strength (psi):

1100 megapascals

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Thread Pitch In Millimeters:

1.25

Surface Finish:

0.8 micrometers

Product Name:

Bolt, close tolerance, hexagon head, alloy steel, 1100 mpa, metric

Material:

Stainless steel

Material Specification:

Na0008 national standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams-qq-p-416, type ii, class 2 (8-14 um thick) national standard single treatment response

Thread Series Designator:

Mj

Specification Data:

80205-na0036 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0