NSN 5306-01-654-6221

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-654-6221 **Thread Class:** 4h6h **Thread Direction:** Right-hand Thread Length: 10.0 inches **Fastener Length:** Between 45.7 millimeters and 46.3 millimeters **Head Style:** Hexagon **Head Height:** Between 3.2 millimeters and 3.5 millimeters Width Between Flats: Between 9.78 millimeters and 10.00 millimeters **Grip Diameter:** Between 5.965 millimeters and 5.990 millimeters **Point Diameter:** Between 4.2 millimeters and 4.7 millimeters **Point Style:** Flat **Internal Drive Style:** W/o internal drive **Thread Diameter:** 6.0 millimeters **Grip Length:** Between 35.8 millimeters and 36.2 millimeters Min. Tensile Strength (psi): 1100 megapascals **Hardness Rating:** 36.0 rockwell c and 40.0 rockwell c **Thread Pitch In Millimeters:** 1.0 **Surface Finish:** 0.8 micrometers **Product Name:** Bolt, close tolerance, hexagon head, alloy steel, 1100 mpa, metric Material: Stainless steel **Material Specification:**

Surface Treatment: Cadmium

Na0008 national standard single material response

NSN 5306-01-654-6221

Close Tolerance Bolt - Page 2 of 2



Surface Treatment Specification:

Ams-qq-p-416, type ii, class 2 (8-14 um thick) national standard single treatment response

Thread Series Designator:

Mj

Specification Data:

80205-na0036 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0