## NSN 5306-01-656-1609

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-656-1609

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.902 inches
Fastener Length:
Between 1.575 inches and 1.605 inches
Head Style:
Hexagon
Head Height:
Between 0.312 inches and 0.327 inches
Width Between Flats:
Between 0.928 inches and 0.940 inches
Grip Diameter:
Between 0.6230 inches and 0.6240 inches
End Application:
1055-01-536-7106
Thread Diameter:
0.6250 inches
Grip Length:
Between 0.678 inches and 0.698 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
160000 pounds per square inch
Product Name:
Bolt, tension
Material:
Steel comp 4140 or steel comp 4340 or steel comp 8740
Material Specification:
Ams6349 assn standard 1st material response or ams6382 assn standard 1st material response or ams6415 assn standard 2nd material
response or ams6484 assn standard 2nd material response or ams6322 assn standard 3rd material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Ams-qq-p-416, type ii, class 2 assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5306-01-656-1609

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0