## NSN 5306-01-656-1669

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-656-1669 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.902 inches **Fastener Length:** Between 2.825 inches and 2.855 inches **Head Style:** Hexagon **Head Height:** Between 0.312 inches and 0.327 inches Width Between Flats: Between 0.928 inches and 0.940 inches **Grip Diameter:** Between 0.6230 inches and 0.6240 inches **End Application:** 1055-01-536-7106 **Thread Diameter:** 0.6250 inches **Grip Length:** Between 1.928 inches and 1.948 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch **Product Name:** Bolt, tension Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 **Material Specification:** Ams6349 assn standard 1st material response or ams6382 assn standard 1st material response or ams6415 assn standard 2nd material response or ams6484 assn standard 2nd material response or ams6322 assn standard 3rd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams-qq-p-416, type ii, class 2 assn standard single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5306-01-656-1669

Shear Bolt - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A003b0