NSN 5306-01-656-3767

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-656-3767

| View Online at https://aerobasegroup.com/nsn/5306-01-656-3767 |
|---|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.646 inches |
| Fastener Length: |
| Between 4.193 inches and 4.223 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.625 inches and 0.640 inches |
| Width Between Flats: |
| Between 1.801 inches and 1.815 inches |
| Grip Diameter: |
| Between 1.2475 inches and 1.2490 inches |
| End Application: |
| 1055-01-536-7106 |
| Thread Diameter: |
| 1.250 inches |
| Grip Length: |
| Between 2.552 inches and 2.572 inches |
| Thready Qty Per Inch (tpi): |
| 12 |
| Min. Tensile Strength (psi): |
| 202000 pounds per square inch |
| Hardness Rating: |
| 39.0 rockwell c and 43.0 rockwell c |
| Surface Finish: |
| 32.0 microinches threads |
| Chamfer Angle: |
| 15.0 degrees |
| Material: |
| Steel comp 4140 or steel comp 4340 or steel comp 8740 |
| Material Specification: |
| Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military |
| specification 3rd material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type ii, class 2 federal specification single treatment response |
| Thread Series Designator: |

Unjf

NSN 5306-01-656-3767

Shear Bolt - Page 2 of 2



| N/a |
|-------------------|
| Unit Of Measure: |
| |
| Demilitarization: |
| Nie |
| No |
| Fiig: |

Mil-std (military Standard):

Mil-s-5626 spec.

Shelf Life: