

View Online at <https://aerobasegroup.com/nsn/5307-00-005-8340>

**Thread Class:**

3a nut thread

**Thread Pitch Diameters:**

+0.2281 to 0.2296 inches stud thread

**Thread Direction:**

Right-hand stud thread

**Thread Length:**

0.425 inches nut thread and 0.455 inches nut thread

**Locking Feature:**

Ring, lock serrated

**Overall Length:**

Between 0.910 inches and 0.970 inches

**Distance From Serrated Portion To Nut End:**

Between 0.485 inches and 0.515 inches

**Distance From Serrated Portion To Stud End:**

0.455 inches

**Distance From Shoulder Portion To Nut End:**

0.425 inches

**Distance From Serrated Portion To End Of Stud Thread:**

Between 0.100 inches and 0.160 inches

**Distance From Cotter Pin Hole Centerline To Nut End:**

0.135 inches second hole

**Cotter Pin Hole Diameter:**

0.070 inches first hole

**Serration Quantity:**

13

**End Application:**

Spec item

**Thready Qty Per Inch (tpi):**

28 stud thread

**Thread Size:**

0.250 inches stud thread

**Surface Finish:**

32.0 microinches nut thd

**Serration Included Angle:**

102.0 degrees

**Material:**

Steel

**Material Specification:**

Ams 5734 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Style Designator:**

Locked in

**Thread Series Designator:**

Uns stud thread

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A051a0