## NSN 5307-00-007-1071

Locked In Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-00-007-1071

**Thread Class:** 

3a nut thread

**Thread Pitch Diameters:** 

+0.2778 to 0.2795 inches stud thread

**Thread Direction:** 

Right-hand stud thread

Thread Length:

0.375 inches stud thread and 0.405 inches stud thread

**Locking Feature:** 

Ring, lock serrated

**Overall Length:** 

Between 1.155 inches and 1.215 inches

**Distance From Serrated Portion To Nut End:** 

Between 0.610 inches and 0.640 inches

**Distance From Serrated Portion To Stud End:** 

Between 0.545 inches and 0.575 inches

**Distance From Serrated Portion To End Of Stud Thread:** 

Between 0.140 inches and 0.200 inches

**Serration Quantity:** 

17

Thready Qty Per Inch (tpi):

28 nut thread

**Hardness Rating:** 

26.0 rockwell c

**Thread Size:** 

0.312 inches stud thread

Surface Finish:

32.0 microinches nut thd

Serration Included Angle:

86.0 degrees

Material:

Steel comp 4130

**Material Specification:** 

Mil-s-6758 military specification single material response

**Surface Treatment:** 

Cadmium

**Surface Treatment Specification:** 

Qq-p-416, type 2, cl 3 federal specification single treatment response

Style Designator:

Locked in

**Thread Series Designator:** 

Uns stud thread

## NSN 5307-00-007-1071

Locked In Stud - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A051a0	

Mil-std (military Standard):

Mil-s-6758 spec.

Shelf Life: