## NSN 5307-00-053-7861

Shouldered Stud - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5307-00-053-7861

| Thread Pitch Diameters:  |
|--|
| +0.7044/+0.7084 inches stud thread   |
| Thread Direction:  |
| Right-hand stud thread   |
| Thread Length:   |
| 1.156 inches nut thread  |
| Shoulder Diameter:   |
| Between 1.125 inches and 1.219 inches  |
| Shoulder Length:   |
| Between 0.188 inches and 0.219 inches  |
| Overall Length:  |
| 3.594 inches   |
| Nut End Shank Length:  |
| 0.188 inches   |
| Distance Across Flats:   |
| 0.938 inches   |
| Thready Qty Per Inch (tpi):  |
| 16 stud thread   |
| Hardness Rating:   |
| Between 98.0 rockwell b and 104.5 rockwell b   |
| Thread Size:   |
| 0.750 inches stud thread   |
| Stud End Shank Diameter:   |
| Between 0.783 inches and 0.786 inches  |
| Nut End Shank Diameter:  |
| Between 0.783 inches and 0.786 inches  |
| Material:  |
| Steel comp 1018 or steel comp 3120   |
| Material Specification:  |
| Astm a108 assn standard 1st material response or astm a331 assn standard 2nd material response |
| Style Designator:  |
| Shouldered   |
| Thread Series Designator:  |
| Uns nut thread   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A051a0   |