NSN 5307-00-074-2433

Shouldered And Stepped Stud - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5307-00-074-2433 **Thread Class:** 2a stud thread **Thread Direction:** Right-hand stud thread Thread Length: 0.208 inches stud thread Shoulder Diameter: Between 0.186 inches and 0.188 inches **Shoulder Length:** 3.564 inches **Overall Length:** 4.120 inches **Nut End Shank Length:** 0.112 inches Thready Qty Per Inch (tpi): 56 nut thread **Thread Size:** 0.112 inches stud thread Stud End Shank Length: 0.030 inches **Stud End Shank Diameter:** 0.030 inches **Surface Finish:** 125.0 microinches **Nut End Shank Diameter:** 0.086 inches **Special Features:** Nut end has a self&locking feature consisting of shoulder 0.117 in. Dia, 0.052 in. W, and undercut 0.107 in. Dia, 0.030 in. W, located 0.238 in. From nut end Material: Steel comp 303se **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Style Designator:** Shouldered and stepped **Thread Series Designator:** Unc stud thread

N/a

Shelf Life:

Unit Of Measure:

NSN 5307-00-074-2433

Shouldered And Stepped Stud - Page 2 of 2



Demilitarization:

No

Fiig:

A051a0